



T60 innovatively combines the design and look of traditional hot rolled Crittall steel window and door profiles with contemporary materials to deliver an enhanced thermal barrier system. The cold formed steel profiles retain the narrow sightlines and iconic profile providing maximum natural light and excellent thermal performance.

Features and Benefits

- Shaped windows and doors including arches, rakes and curves
- Fully welded, seamless frame construction
- Slim profiles maximise glass area
- Factory applied architectural grade polyester powder coating
- Excellent thermal performance
- High acoustic attenuation
- Range of profiled beads for internal or external glazing
- Side, top and bottom hung, horizontal and vertical pivoting windows together with single and double leaf doors
- Hardware designed for heritage and contemporary projects

Quick View

Material	Steel, cold rolled
Glass Thickness	38mm / 1 1/2" double and triple glazing
Suitability	All market sectors & building styles
Finish	Full range of RAL/BS colours
Thermal	As low as U value 0.8 W/m ² K
Acoustic	Up to Rw46dB
Air Permeability	Up to 600 Pa / 12.53 PSF
Water Tightness	Up to 300 Pa / 6.24 PSF
Wind Resistance	Up to 2500 Pa / 52.23 PSF
Quality Management	ISO 9001

VISION | INNOVATION | SOLUTIONS