



T60 innovatively combines the design and look of traditional hot rolled Crittall steel window profiles with contemporary materials to deliver an enhanced thermal barrier system. The cold formed steel frames retain the narrow sightlines and iconic profile providing maximum natural light and excellent thermal performance.

Features and Benefits

- Fully welded, seamless frame construction
- Slim profiles maximise glass area
- Factory applied architectural Duralife® polyester powder coating
- Excellent thermal performance offering up to $U_w 0.8 \text{ W/m}^2/\text{K}$
- High acoustic attenuation up to $R_w 45\text{Db}$
- Strong, robust profiles that resist forced entry
- Side hung, top hung, projected top hung, fixed and multi-light configurations
- Hardware designed for heritage and contemporary projects including multi-point locking

Quick View

Material	Steel, cold rolled
Glass Thickness	Up to 32mm / 1-1/4"
Suitability	All market sectors & building styles
Finish	Full range of RAL/BS colours
Thermal	Up to U_w value $0.8 \text{ W/m}^2/\text{K}$ / 0.14 BTU
Acoustic	Up to $R_w 45\text{dB}$
Air Permeability	Up to Class 4 600 Pa/12.53 PSF
Water Tightness	Up to Class 9A 600 Pa/12.53 PSF
Wind Resistance	Up to Class 5 2000 Pa/41.77 PSF
Quality Management	ISO 9001

VISION | INNOVATION | SOLUTIONS

t: +44 (0) 1376 530 800 e: hq@crittall-windows.co.uk

Crittall Windows Limited, Francis House, Freebournes Road, Witham, Essex, CM8 3UN